

FILTER & PUMP COMBO



Emaux Filter & Pump Combos are equipped with the most optimal combination of our filters and pumps. The combination fosters energy efficiency and outstanding filtration process. The synergistic effect of our combos allows users to have an ease of mind as well as trouble-free installation.



www.emaux.com.hk

FILTER & PUMP COMBO



FSP-4W SERIES FILTRATION COMBO FSP-4W系列沙缸连水泵组合



Maximum Working Pressure 最大工作压力: 200 kPa (28psi)
 Factory Testing Pressure 工厂测试压力: 300 kPa (44psi)
 Maximum Water Temperature 最大操作温度: 40°C (104°F)
 Size of Silica Sand 石英沙规格: 0.5 - 0.8mm

TECHNICAL CHARACTERISTICS 参数表

Code 产品编码	Model No 型号	A mm	B mm	Filter 沙缸	Pump 水泵	Valve Connections 接管尺寸	Max flow Rate 设计流量	Sand (kg) 装沙重
88830206	FSP350-4W	565	590	P350	SS020	1-1/2 inch 50mm	72 lpm 4.32 m ³ /h	20
88830207	FSP400-4W	760	825	P400	SS033	1-1/2 inch 50mm	100 lpm 6.00 m ³ /h	35
88830208	FSP450-4W	760	890	P450	SS050	1-1/2 inch 50mm	135 lpm 8.10 m ³ /h	45
88830209	FSP500-4W	760	924	P500	SS075	1-1/2 inch 50mm	185 lpm 11.10 m ³ /h	85
88830210	FSP650-4W	760	932	P650	SS100	1-1/2 inch 50mm	250 lpm 15.00 m ³ /h	145

FSP-6W SERIES FILTRATION COMBO FSP-6W系列沙缸连水泵组合



Maximum Working Pressure 最大工作压力: 200 kPa (28psi)
 Factory Testing Pressure 工厂测试压力: 300 kPa (44psi)
 Maximum Water Temperature 最大操作温度: 40°C (104°F)
 Size of Silica Sand 石英沙规格: 0.5 - 0.8mm

TECHNICAL CHARACTERISTICS 参数表

Code 产品编码	Model No 型号	A mm	B mm	Filter 沙缸	Pump 水泵	Valve Connections 接管尺寸	Max flow Rate 设计流量	Sand (kg) 装沙重
88830406	FSP350-6W	565	600	P350	SS020	1-1/2 inch 50mm	72 lpm 4.32 m ³ /h	20
88830407	FSP400-6W	760	759	P400	SS033	1-1/2 inch 50mm	100 lpm 6.00 m ³ /h	35
88830408	FSP450-6W	760	813	P450	SS050	1-1/2 inch 50mm	135 lpm 8.10 m ³ /h	45
88830409	FSP500-6W	760	856	P500	SS075	1-1/2 inch 50mm	185 lpm 11.10 m ³ /h	85
88830410	FSP650-6W	760	991	P650	SS100	1-1/2 inch 50mm	250 lpm 15.00 m ³ /h	145

FSF-6W SERIES FILTRATION COMBO FSF-6W系列沙缸连水泵组合



Maximum Working Pressure 最大工作压力: 250 kPa (36psi)
 Factory Testing Pressure 工厂测试压力: 400 kPa (58psi)
 Maximum Water Temperature 最大操作温度: 43°C (109°F)
 Size of Silica Sand 石英沙规格: 0.5 - 0.8mm

TECHNICAL CHARACTERISTICS 参数表

Code 产品编码	Model No 型号	A mm	B mm	Filter 沙缸	Pump 水泵	Valve Connections 接管尺寸	Max flow Rate 设计流量	Sand (kg) 装沙重
88830101	FSF350-6W	565	600	V350	SS033	1-1/2 inch 50mm	72 lpm 4.32 m ³ /h	20
88830102	FSF400-6W	760	759	V400	SS050	1-1/2 inch 50mm	100 lpm 6.00 m ³ /h	35
88830103	FSF450-6W	760	813	V450	SS075	1-1/2 inch 50mm	135 lpm 8.10 m ³ /h	45
88830104	FSF500-6W	760	856	V500	SC100	1-1/2 inch 50mm	185 lpm 11.10 m ³ /h	85
88830105	FSF650-6W	760	991	V650	SC150	1-1/2 inch 50mm	250 lpm 15.00 m ³ /h	145